










- CABEZA: Aluminio Al Mg 3,5
- VÁSTAGO: Acero protección cincado A1K



UNE - EN ISO 15977

d1 Ø mm	L Nominal mm	€ 1.000 PCS.	 mm	d2 Ø mm	K mm	W Ø mm	EMBALAJE		 E MIN. mm MÁX	 (N)	 (N)	CÓDIGO ARTÍCULO
							 Interior	 Exterior				
5,0	6	27,90	5,10	9,50	1,60	2,65	500	3.000	0,5 - 3,0	2.150	3.100	01010005006
	8	31,80					500	3.000	3,0 - 4,5			01010005008
	10	35,30					500	3.000	4,5 - 6,0			01010005010
	12	39,80					500	3.000	6,0 - 8,0			01010005012
	14	47,40					250	2.000	8,0 - 10,0			01010005014
	16	51,40					250	2.000	10,0 - 12,0			01010005016
	18	56,70					250	1.500	12,0 - 14,0			01010005018
	20	62,80					250	1.500	14,0 - 16,0			01010005020
	25	71,30					200	1.200	16,0 - 21,0			01010005025
	30	83,60					200	1.200	21,0 - 25,0			01010005030
	35	95,20					150	900	27,0 - 30,0			01010005035
	40	108,80					150	900	30,0 - 35,0			01010005040
45	120,50	100	600	35,0 - 40,0	01010005045							
50	136,80	100	600	40,0 - 45,0	01010005050							
6,0	8	69,00	6,10	12,00	1,80	3,20	250	1.500	2,0 - 3,0	3.200	4.600	01010006008
	10	72,10					250	1.500	3,0 - 5,0			01010006010
	12	75,10					250	1.500	5,0 - 7,0			01010006012
	14	77,30					250	1.500	7,0 - 9,0			01010006014
	16	79,40					250	1.500	9,0 - 11,0			01010006016
	18	81,60					200	1.200	11,0 - 13,0			01010006018
	20	87,10					200	1.200	13,0 - 15,0			01010006020
	25	95,90					200	1.200	15,0 - 20,0			01010006025
	30	104,60					150	900	20,0 - 25,0			01010006030
	35	125,70					100	600	25,0 - 30,0			01010006035
6,4	12	81,60	6,50	13,00	2,20	3,60	250	1.500	3,0 - 6,0	3.400	4.850	01010006412
	15	89,90					250	1.500	6,0 - 9,0			01010006415
	18	97,60					200	1.200	9,0 - 12,0			01010006418
	22	106,50					200	1.200	12,0 - 16,0			01010006422
	26	133,20					150	900	16,0 - 20,0			01010006426
	30	171,20					150	900	20,0 - 22,0			01010006430
	35	205,30					100	600	24,0 - 29,0			01010006435
	40	Consultar					500	29,0 - 34,0	G1010006440			
	50	579,50					500	29,0 - 42,0	01010006450			
7,8	15	113,60	8,00	13,50	2,20	3,60	1.000	6,0 - 9,0	5.000	7.500	G1010007815	
	22	130,10					1.000	9,0 - 16,0			G1010007822	

Ensayos realizados según EN ISO 14589