

TECHNICAL DATASHEET

SAFETY GLASSES CRACK'R

Clear AS – Ref. 887639 Clear AS AF – Ref. 887640



Description:

Lightweight, comfortable safety spectacles in a wrap-around, rimless design. Thin and flexible temples. Molded nose bridge. Protects against UVA UVB, 99.9% spectral filter. Weight: 23.3

g. Colour:

Clear lens. Black temples.

Strong points:

Curved lenses designed to provide an excellent field of vision.

Characteristics:

Lenses: PC - 2 mm - Curve 10.5

Temples: PC

Anti-scratch and anti-fog (887640 only) coatings.

Lens marking: 2C-1.2 G 1 FT CE Frame marking: UKCA EN166 FT

Certification: EN166: 2001

UK CA

Packing:

Cartons of 300 units.

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case. STORAGE:

All products must be stored in a dry and clean environment.

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for spectacles.

T. The letter T, immediately after the mechanical strength symbol, authorizes use for high speed particles at extreme temperatures.