

410AS Brocas serie corta de acero HSS cilindradas, en pulgadas

ANSI B94

R ≤ 650 N/mm²
HV 750÷820

	art.	Ø "	L mm	L1 mm	g
004100371	410AS 1/16	1/16	48	22	1
004100372	410AS 5/64	5/64	51	25	1
004100373	410AS 3/32	3/32	57	32	2
004100374	410AS 7/64	7/64	67	38	2
004100375	410AS 1/8	1/8	70	41	3
004100376	410AS 9/64	9/64	73	44	4
004100377	410AS 5/32	5/32	79	51	5
004100378	410AS 11/64	11/64	83	54	6
004100379	410AS 3/16	3/16	89	59	9
004100380	410AS 13/64	13/64	92	62	10
004100381	410AS 7/32	7/32	95	64	11
004100382	410AS 15/64	15/64	98	67	15
004100383	410AS 1/4	1/4	102	70	16
004100384	410AS 17/64	17/64	105	73	19
004100385	410AS 9/32	9/32	108	75	20
004100386	410AS 19/64	19/64	111	78	25
004100387	410AS 5/16	5/16	114	81	28
004100388	410AS 21/64	21/64	117	84	29
004100389	410AS 11/32	11/32	121	87	34
004100390	410AS 23/64	23/64	124	89	40
004100391	410AS 3/8	3/8	127	92	46

